



Maximum Allowable Deck Spans **BLACK LABEL™** Decking

The following chart indicates the engineered maximum allowable decking spans for the combined Black Label™ group of decking products based on the lowest collective mechanical properties of all species sold under the Black Label brand.

Referenced maximum allowable deck spans are specific to Black Label™ brand decking products and grading rules and should not be relied on for Non-Black Label™ hardwood decking products.

MAXIMUM ALLOWABLE SPANS				
BLACK LABEL™ DECKING				
PREMIUM SELECT ARCHITECTURAL GRADE	Deck	Loading		
		60 psf	100 psf	500 psf
	Thickness	60 psf	100 psf	500 psf
	0.75 in	27 in	24 in	12 in
	1.00 in	39 in	33 in	18 in
	1.50 in	57 in	48 in	27 in
	2.50 in	96 in	81 in	48 in
	3.50 in	135 in	114 in	66 in

Deck Live Load Deflection is limited to L/360, total deflection is limited to L/240, L is the span length.

Deflection (bounce) is subjective. It must be noted that deflection reduces by reducing the decking span.

Building Inspectors should request signed engineering documents to verify basis of structural design and building code compliance. Black Label™ Decking, Signed and Stamped engineering documents are available upon request.



6200 Tomken Road, Mississauga
L5T 1X7, ON, CA
Phone: (905) 672-8000
www.wearretropical.com

