

TROPICAL

**STANDARD MATERIAL SAFETY DATA SHEET (MSDS)
FURNISHED BY TROPICAL FOREST PRODUCTS
HAZARD WARNING FOR UNTREATED WOOD PRODUCTS**

TRADE NAME: Wood Dust

SYNONYMS: None

CASE NO.: None

DESCRIPTION

Particles generated by any manual or mechanical cutting or abrasion process performed on wood.

PHYSICAL DATA

Boiling Point	Not Applicable.
Specific Gravity	Variable (dependent on wood species and moisture content).
Vapor Density	Not Applicable.
% Volatiles by Volume	Not Applicable.
Melting Point	Not Applicable.
Vapor Pressure	Not Applicable.
Solubility in H ₂ O (% by wt.).....	Insoluble.
Evaporation Rate (Butyl Acetate = 1)	Not Applicable.
pH	Not Applicable.
Appearance and Odor	Light to dark colored granular solid. Color and odor are dependent on the wood species and time since dust was generated.

FIRE AND EXPLOSION DATA

Flash Point	Not Applicable.
Auto-Ignition Temperature	Variable (typically 400-500°F).
Explosive Limits in Air	40 grams/m ³
Extinguishing Media	Water, CO ₂ , Sand.
Special Fire Fighting Procedures	Use water to wet down wood dust to reduce the likelihood of ignition or dispersion of dust into the air. Remove burned or wet dust to open area after fire is extinguished.
Unusual Fire and Explosion Hazard	Wood dust is a strong to severe explosion hazard if a dust "cloud" contacts an ignition source.

TROPICAL

HEALTH EFFECTS INFORMATION

Exposure Limit ¹	ACGIH TLV®: TWA – 5.0 mg/m ³ ; STEL (15 min.) – 10 mg/m ³ (softwood); TWA – 1.0 mg/m ³ (certain hardwoods such as beech and oak). OSHA PEL: TWA – 5.0 mg/m ³ ; STEL (15 min.) – 10 mg/m ³ (all soft and hard woods, except Western Red Cedar. Western Red Cedar: TWA – 2.5 mg/m ³
Skin and Eye Contact	Wood dust can cause eye irritation. Various species of wood dust can elicit allergic contact dermatitis in sensitized individuals.
Ingestion	Not applicable.
Skin Absorption	Not known to occur.
Inhalation	May cause nasal dryness, irritation and obstruction. Coughing, wheezing and sneezing; sinusitis and prolonged colds have also been reported.
Chronic Effect	Wood dust, depending on species, may cause dermatitis on prolonged, repetitive contact; may cause respiratory sensitization and/or irritation. Prolonged exposure to wood dust has been reported by some observers to be associated with nasal cancer. Wood dust is not listed as a carcinogen by LARC, NTP, ACGIH or OSHA.

REACTIVITY DATA

Conditions Contributing to Instability	Stable under normal conditions.
Incompatibility	Avoid contact with oxidizing agents and drying oils. Avoid open flame. Product may ignite at temperatures in excess of 400° F.
Hazardous Decomposition Products	Thermal oxidative degradation of wood produces irritating and toxic fumes and gases, including CO, aldehydes and organic acids.
Conditions Contributing to Polymerization	Not Applicable.

¹ Although OSHA's Air Contaminants Rule, including OSHA's wood dust PELs, was struck down in ALF-CIO v. OSHA, 965 F. 2d 962 (11th Cir. 1992), a number of states have incorporated those provisions in their state plans. Additionally, OSHA has announced

TROPICAL

that it may cite companies under the OSH Act general duty clause under appropriate circumstances for non-compliance with these levels.

PRECAUTIONS AND SAFE HANDLING

Avoid eye contact.

Avoid repeated or prolonged contact with skin. Careful bathing and clean clothes are indicated after exposure.

Avoid prolonged or repeated breathing of wood dust in the air.

Avoid contact with oxidizing agents and drying oils.

Avoid open flame.

GENERALLY APPLICABLE CONTROL MEASURES

Ventilation: Provide adequate general and local exhaust ventilation to maintain healthful working conditions.

Wear goggles or safety glasses. Other protective equipment such as gloves and approved dust respirators may be needed depending upon dust conditions.

EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush with water to remove dust particles. If irritation persists, get medical attention.

Skin: If a rash or persistent irritation or dermatitis occur, get medical advice where applicable before returning to work where wood dust is present.

Inhalation: Remove to fresh air. If persistent irritation, severe coughing, or breathing difficulties occur, get medical advise before returning to work where wood dust is present.

Ingestion: Not applicable.

SPILL/LEAK CLEAN UP PROCEDURES

Sweep or vacuum spills for recovery or disposal; avoid creating dust conditions. Provide good ventilation where dust conditions may occur. Place recovered wood dust in a container for proper disposal.

IMPORTANT: The information and data contained herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. AF&PA makes no warranty of any kind, express or implied, concerning the accuracy or completeness of the information and data herein. AF&PA will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.

TROPICAL

