



# TROPICAL

---

maintains optimum initial adhesion to substrates when used within one year from the date of manufacture.

6725\$

7URSLFDO)RUHVW3UR&FWVHFN7DSH should be stored in the original, unopened container at ambient temperatures between 40°F to 90°F (5°C to 32°C). Storage area should remain dry and out of direct sunlight. Do not remove materials from original containers until ready for use. Do not double stack pallets.

35(35\$,21

All surfaces shall be clean, dry and free of any foreign materials. The surface shall be free of gaps, sharp edges and protrusions.

Metal surfaces may need to be solvent wiped and/or abraded to achieve optimum adhesion.

<sup>1</sup> Note: ,WLV recommendHVR test substrates for adhesion prior to full application.

<sup>2</sup> Note: installation over damp surfaces may result in the formation of bubbles/air pockets under the 7URSLFDO)RUHVW3UR&FWVHFN7DSH due to moisture drive, the use of a roller will help to remove the bubbles and air pockets.

\$3/,21

Cut 7URSLFDO)RUHVW3UR&FWVHFN 7DSH to desired length and peel off 3" to 6" of the poly film release liner from bottom, taking care not to allow the adhesive to come into contact with itself or any foreign matter. Center the material on the top of the joist and use roller to smooth out any wrinkles, creases or air bubbles. Apply firm pressure with a hand roller or "J" roller to ensure adequate adhesion. Pressure is essential to eliminate any wrinkles or trapped air bubbles. Overlaps should be a minimum of 2 inches on side lap, and 4 inches on end lap.

&\$83

Dispose of waste in accordance to local requirements. Control worksite so that boxes and release liner do not present a hazard.

Packaging materials and release liner can be recycled.

&7,21

**Tropical Forest Products ec Tape** has an aggressive adhesive, we recommend removing 3" to 6" of the poly film release liner at a time while installing to help prevent the tape from sticking to itself.

PVC and TPO type roofing membranes may contain high concentrations of plasticizers that may react with the Synthetic Butyl adhesive.

Do not adhere 7URSLFDO)RUHVW3UR&FWVHFN7DSH to skin, removal may cause loss of hair and/or bleeding.

ProSHUSURWHFWLRCEXSD safety glasses and gloves DUHUHFRPPHG

Do not stretch 7URSLFDO)RUHVW3UR&FWVHFN7DSH